

Selection of reels for eMobility

- an independently operating charging station -

FT 350



- charging station/wallbox with cable management
- stable design in plastic housing
- with integrated charging electronics (Plug&Charge)
- with thermal protection
- 8m charging cable with type 2 charging coupling
- 2m connecting cable without plug connection
- incl. swivel wall mounting bracket
- rotating ceiling holder as accessory available

The charging station/wallbox with cable management must be connected by a qualified electrician. The device must be protected with a FI type B or type A-EV.

Order-No.	Item	Protection class	Cable (m)	Cable type	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
660 91 405 000	FT 350.0416.I02.0820.0101-0000	IP42	8	3G2,5+1x0,5qmm	230V	3680W	3680W	7,82
660 91 615 000	FT 350.0616.I02.0820.0201-0000	IP 42	8	5G2,5+1x0,5qmm	400V	7520W	11kW	8,87

FT 038



- charging station/wallbox with cable management
- stable, open design made of plastic
- with integrated charging electronics (Plug&Charge), contactor
- optional integrated residual current monitoring 6mA**
- with thermal protection
- 8m charging cable with type 2 charging coupling
- 2m connecting cable without plug connection
- incl. swivel wall mounting bracket
- rotating ceiling holder as accessory available

The charging station/wallbox with cable management must be connected by a qualified electrician.

The device must be protected with a FI type B or type A-EV.*
The device must be protected with a FI type A.**

Order-No.	Item	Protection class	Cable (m)	Cable type	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
620 91 615 000	FT 038.0516.I02.0820.0205-0000*	IP44	8	5G2,5+1x0,5qmm	400V	11kW	11kW	19,89
620 92 615 000	FT 038.0516.I03.0820.0205-0000**	IP44	8	5G2,5+1x0,5qmm	400V	11kW	11kW	18,81